

Introducing...



- 125,000 Btu output
- 1000 CFM blower provides gentle heat
- Integral thermostatic control
- Oxygen detection system safety control
- Multifunctional  
(heater, fan only, staging table)
- Odor free
- 4 wheels for greater portability & maneuverability



- Powder coated steel base
- Durable molded high density polymer tabletop
- Electronic ignition with lighted Off/On switch



**The Tent Event 125 provides quiet, gentle for weddings, receptions, business meetings, church gatherings, parties, and other tent events. A single unit will heat a 40' x 60' x 10' tent. Simply combine with additional units to provide comfortable heat for larger size tents and gatherings.**

**The first heater certified for tent event usage. For use inside the tent without ductwork. 20% quieter than some competitive products.**





#### Specifications

Model No.	TB116
BTU	125,000 Btu
Blower CFM	1,000 CFM
Size	41 3/4" L x 24" D x 36" H
Weight	115 Lbs
Motor	1/4 H.P. at 1100 RPM
Required electrical supply	115 volts
Amperage (Start/Continuous)	5amps/3amps
Noise	64 dbA
Tank size	100 lb. min.
Hose length	15'
Emissions	0.011 CO-AF%
Table surface size	41 3/4" L x 24" D
Aux. outlet	2-15 amp grounded outlets
Rec. extension cord size	14 Gauge for 100 ft. or less
Ignition	Electronic
Tent size heated	40' x 60' x 10'
CSA standards	Construction and tent event



Ergonomically designed lift handles for portability

Durable rugged molded polymer top

Only heater designed and certified to be used inside a gathering tent

Certified to both the construction and new tent event standard

Re-circulates heated air for 99% efficiency



#### TENT VS. CONSTRUCTION STANDARDS

Standard	Tent	Construction
Oxygen Depletion Safety Shutoff Devices	Y	N
CO concentration	<.02%	<.08%
Approved for use in Tent	Y	N
Label w/ sq. in. of required ventilation	Y	N
Safety Circuit Analysis	Y	N
Surface Temperature Standards	<180° F	None
Test of Clothing Ignition Potential	Y	N
Discharge Air Temperature	<280° F	None

